

# PJ1173

## HIGH BRIGHTNESS MULTIMEDIA PROJECTOR

WITH NETWORK CONTROL

## Multifunction versatility in an outstanding projector.

ViewSonic's PJ1173 delivers maximum impact for large-venue presentations. With 5,000 LUMENS and 1000:1 contrast ratio (typ), this PREMIUM PROJECTOR is ideally suited for conference rooms, lecture halls, religious sanctuaries and boardrooms. The PJ1173 is full-featured with native XGA 1024x768 resolution, advanced image processing, manual lens shift, horizontal and vertical (auto) keystone correction, and HDMI input to support up to 1080p signals. The image reversing function offers versatile installation options. Network connectivity allows you to REMOTELY CONTROL AND MANAGE YOUR PROJECTOR and the 4x4-watt SRS® WOW STEREO SPEAKERS give your presentations powerful sound. The security bar and PIN lock guard against theft and unauthorized use. The PJ1173 is the full-featured choice for dynamic presentations and smooth video entertainment in large venues.



### OUTSTANDING PRESENTATIONS

#### > Ultimate video source flexibility

Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on another display.

#### > Network control through RJ-45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.

#### > Enhanced security features

PIN lock feature prevents unauthorized use. Kensington® security lock and a security bar allow you to secure the projector to deter theft.

#### > The perfect image in any setting

Digital horizontal and vertical (auto) keystone correction, manual lens shift, and optical zoom ensure the perfect image in any room.

#### > Superior 16-watt stereo sound

Four 4-watt speakers with SRS(R) WOW technology for panoramic 3D sound.

#### > Optional lenses make installation flexible

Easy-to-install lens options allow you to project in rooms of virtually any size.

#### > Easy maintenance

Easy access to the lamp and filter covers even when the projector is mounted.

#### > 3+1+1 warranty

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® Service and one-year limited lamp warranty.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference™ 

# PJ1173

## High Brightness Multimedia Projector



### Optional Accessories

Replacement lamp.....RLC-038

Screen size [inch (m)]	4:3 screen			
	Projection distance [m (inch)]		Screen height [cm (inch)]	
	min.	max.	down	up
30 (0.8)	0.9 (35)	1.1 (42)	5 (2)	41 (16)
60 (1.5)	1.8 (71)	2.2 (86)	9 (4)	82 (32)
80 (2.0)	2.4 (96)	2.9 (115)	12 (5)	110 (43)
100 (2.5)	3.0 (120)	3.7 (144)	15 (6)	137 (54)
200 (5.1)	6.1 (241)	7.4 (291)	30 (12)	274 (108)
300 (7.6)	9.2 (363)	11.1 (437)	46 (18)	411 (162)
350 (8.9)	10.8 (424)	13.0 (510)	53 (21)	480 (189)

  

Screen size [inch (m)]	16:9 screen			
	Projection distance [m (inch)]		Screen height [cm (inch)]	
	min.	max.	down	up
30 (0.8)	1.0 (38)	1.2 (46)	-1 (0)	39 (15)
60 (1.5)	2.0 (78)	2.4 (94)	-2 (-1)	77 (30)
80 (2.0)	2.6 (104)	3.2 (126)	-3 (-1)	103 (41)
100 (2.5)	3.3 (131)	4.0 (157)	-4 (-2)	129 (51)
200 (5.1)	6.7 (263)	8.0 (317)	-8 (-3)	257 (101)
300 (7.6)	10.0 (395)	12.1 (476)	-12 (-5)	386 (152)
350 (8.9)	11.7 (462)	14.1 (556)	-15 (-6)	450 (177)

Model No.VS12109

<b>PROJECTOR</b>	Type	0.8 inches (x3) Poly-Si TFT with Micro Lens
	Resolution	XGA 1024X768
	Lens	Manual zoom/focus (1:1.2X)
	Support Resolution	1600X1200 (compressed)
<b>DISPLAY</b>	Keystone	Vertical Digital keystone correction: / 40 degrees
	Size	30"-500" (Diagonal)
	Throw Distance	0.87m-15.2m
	Throw Ratio	1.97(wide) & 2.16(tele)
	Lamp	275 watt ACHID
	Brightness	5000 Lumens
	Contrast Ratio	1000:1
	Aspect Ratio	4:3 & 16:9
<b>COLOR GAMUT</b>		98% NTSC (1931 CIE)
<b>AUDIO</b>	Speakers	4w X4 Stereo
<b>INPUT SIGNAL</b>	RGB	RGB analog
	Video	NTSC, PAL, SECAM
	HDTV Signal	HDTV (480i/p, 576i/p, 720p, 1080i)
	Frequency	Fh:31-92 KHz, Fv:56-120 Hz
<b>COMPATIBILITY</b>	PC	VGA to UXGA
	Mac	Up to 832X624 (may require Mac Adapter)
<b>CONNECTOR</b>	RGB Input	15-pin D-sub (X1) ,5-BNC x 1
	RGB Output	15-pin D-sub (X1)
	Digital Input	HDMI 1.3 (X1) (support with HDCP compliance)
	Composite Video	RCA Jack X 1
	S-Video	Mini-Din 4-pin X 1
	Componet Video	RCA Jack (X1 set)
	Audio Input	3.5 mm Stereo Mini Jack (X2) for RGB, RCA (L/R) Jack (X1) for Video
	Audio Output	3.5 mm Stereo Mini Jack (X1)
	Control	RS-232 (9 Pin D-sub) X1 ,RJ45
	USB	Type B (for mouse control only) X1
	<b>POWER</b>	Voltage
	Consumption	460W (Typical)
<b>NOISE LEVEL</b>		36dB (Typical)
<b>LANGUAGE</b>	LANGUAGE	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Traditional Chinese, Turkish
<b>CONTROLS</b>	Basic	Standby/On, input, menu
	Remote	Brightness, Contrast, Gamma, Color Temp, Color, Tint, Sharpness, Active Iris, My Memory, Aspect, Over Scan, V position, H position, H Phase, H size, Auto Adjust Execute, Progressive, Video NR, 3D-YCS, Color Space, Component, Video Format, HDMI, Frame Lock, RGB IN, Resolution, Auto Keystone Execute, Keystone V, Keystone H, Whisper, Mirror, Volume, Treble, Bass, SRS WOW, Speaker, Audio, HDMI Audio, Language, Menu Position, Blank, Start up, Myscreen, Myscreen Lock, Message, Source Name, Auto Search, Auto Keystone, Auto On, Auto off, Lamp time, Filter Time, My Button, Service (Fan Speed, Auto Adjust, Ghost, Filter Message, Lens Type, Key Lock, Remote Receiv, Remote FREQ., Information, Factory Reset), Security (Security password change, Myscreen password change, PIN Lock, Transition Detector), Network (DHCP, IP address, Subnet mask, Default gateway, Time difference, Date and time, e-shot, Information, Service)
<b>OPERATING CONDITION</b>	Temperature	5°C - 35°C 41°F - 95°F
	Humidity	10% - 85% non-condensing
<b>DIMENSIONS (W x D x H)</b>	Physical (mm)	418mm X 319mm X 139mm
		16.45" X 12.56" X 5.47"
<b>WEIGHT</b>	Net	7.1 kgs (15.61 lbs)
<b>REGULATIONS</b>		UL60950-1/C-UL, FCC part 15 Class B, CE marking EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC directive), DEMKO-GS, WEEE, RoHS, C-Tick (Australia / New Zealand)

**Headquarters:**  
381 Brea Canyon Road,  
Walnut, CA 91789-0708  
www.viewsonic.com

**Asia Pacific**  
9F, No. 192, Lien Chen Road,  
Chung Ho, 235 Taipei, Taiwan, R.O.C  
www.viewsonic.com.tw/

**ViewSonic Korea**  
#907, 9F, Hyundai HYEL, 2-36,  
Hangangro 2-ga,  
Yongsan-gu, Seoul, Korea 140-871  
kr.viewsonic.com

**ViewSonic Singapore**  
221 Henderson Road,  
#04-08 Henderson Building,  
Singapore 159557  
www.viewsonic.com.sg/

**ViewSonic Australia**  
Unit 4, 44 Dickson Ave, Artarmon,  
NSW 2064, Australia  
www.viewsonic.com.au/

**ViewSonic India**  
M-28, Commercial Complex (M-Block Market),  
3rd floor, Greater Kallash-II, N Delhi - 110 048, India  
in.viewsonic.com

**ViewSonic Middle East**  
LOB 13 Office 8, PO Box 17625,  
Jebel Ali, Dubai, U.A.E.  
http://ap.viewsonic.com/mee/

**ViewSonic®**  
See the difference™ 