

PJD6251

LIGHT BRIGHT AND PORTABLE PROJECTOR

120HZ, 3D-READY

Brilliant, bright image. Easy maintenance.

The advanced PJD6251 120Hz / 3D ready DLP projector includes BrilliantColor™ technology to produce more vibrant colors. The HDMI port provides high quality content. And the ultra-high brightness and contrast ratios make this projector shine in virtually any lighting situation. This projector offers table top and ceiling or wall mount options. Making it ideal for classrooms and meeting rooms. The top load lamp and filter-less design provides for easy maintenance and low total cost of ownership. RJ-45 connectivity enables remote network control, while the extensive input options and integrated 2x5W speaker provide for effective presentations or classroom lessons. This projector also features closed captioning for the hearing impaired. Choose the PJD6251 for both classroom or corporate settings.



Versatile presentations anywhere

- > **Bright in virtually any setting with lumens**
Packs 3700 ANSI lumens in just 2.9kg(6.3lb), and with a high 2800:1 contrast ratio, your presentations are guaranteed to be vibrant even in the brightest office environment.
- > **BrilliantColor technology**
Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like colour, sharp graphics and outstanding video. The sophisticated 6-segment colour wheel enriches the yellow colour performance that is key to accurate and vivid color reproduction.
- > **Eco-mode extends lamp life hrs**
Extend the life of your lamp up to 5000 hours** and reduce noise output.
- > **Network control through RJ-45**
Remotely schedule, manage and monitor the projector and its lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.
- > **Off to go**
The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

PJD6251

LIGHT BRIGHT AND PORTABLE PROJECTOR

ViewSonic® See the difference™ 

Model No.VS12585



Optional Accessories

- >Replacement Lamp.....RLC-051
- >Wireless G Presentation Gateway.....WPG-350
- >Ceiling mount.....WМК-025

Projection Distance		4 : 3 Screen Screen Size			
		Wide		Tele	
M	feet	m	inch	m	inch
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259

DISPLAY	Type	0.55" Digital Micromirror Device(DLP™)
	Resolution	XGA 1024x768(Native) / UXGA 1600x1200(compressed)
	Lens	1.2x Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction:+/- 40 degrees
	Display Size(diagonal)	30"-300"
	Throw Distance	1m-10m
	Throw Ratio	1.6-1.9
	Lamp	280watt(RLC-049)
	Lamp Life(Normal / Eco Mode)	4000 / 5000(hours)
	Brightness	3700 Lumens
	Contrast Ratio	2800:1
	Aspect Ratio	4:3(native) & 16:9
	Color Depth	30 bits, 1.073 B Colour(10+10+10)
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Gamut	85 % NTSC 1931 CIE
AUDIO	Speaker	5W x2
INPUT SIGNAL	Computer and video	NTSC M(3.58MHz), 4.43MHz, PAL(B, D, G, H, I, M, N, 60), SD 480i and 576i(24fps, 25fps and 30fps), ED 480p and 576p(24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh:31-100KHz, Fv:50-120Hz
COMPATIBILITY	PC	VGA to UXGA
	Mac	Up to 1152x864(may require Mac Adapter)
CONNECTOR	RGB Input	2 x 15-pin mini D-sub
	HDMI	1 x HDMI 1.3
	RGB Output	1 x 15-pin mini D-sub
	Composite Input	1 x RCA jack
	S-Video Input	1 x 4-pin mini-DIN
	Audio Input	2 x 3.5mm mini jack
	Audio Output	1 x 3.5mm mini jack
	Control	1 x RS-232(9 Pin D-sub) / 1 x RJ45
	USB	TYPE B(Firmware upgrade)
	Power	12 V DC Connector
POWER	Voltage	90~240VAC(Auto Switching), 50 / 60Hz(universal)
	Power Consumption	320W(Typical) / <1W(Stand-by mode)
LANGUAGE		English/ Dutch/ French/ Spanish/ Italian/ Korean/ Thai/ Portuguese/ T. Chines/ S. Chinese/ Japanese/ Russian/ German/ Swedish/ Turkish/ Finnish/ Polish
CONTROLS	Basic	POWER, Keystone/ Arrow keys, Left/ BLANK, MENU/ EXIT, Right/ Panel key lock, AUTO, MODE/ ENTER, SOURCE
	OSD	Picture: Brightness, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert. Computer Image: Frequency, tracking, H position, V position. Video Image: Saturation, sharpnes, tint. Setting: Manu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, ECO mode, high altitude, OSD timeout. Advance: Blank screen, password word, screen capture, start up screen, text shot, digital zoom, DCR, close captions, brilliant color,
OPERATING CONDITIONS	Temperature	0°C-40°C(32°F-104°F)
	Humidity	10%-80%(non-condensing)
	Altitude	0~1800m(6000ft), operational up to 3048m(10,000ft) at reduced reliability and performance
NOISE LEVEL	Normal / Eco Mode	34dB / 32dB
DIMENSIONS (W x H x D)	Physical	280x114x218(mm) / 11x4.5x8.58(inch)
WEIGHT	Net	2.9kg (6.3lb)
REGULATIONS		CB, ROHS, WEEE, UL / cUL, FCC-B, ICES-003, IRAM(Argentina), NOM, PSB, C-tick, CE, TUV, GOST-R, Hygienic, UKrSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Soft case, Quick Start Guide, ViewSonic Wizard CD(with User Guide)
WARRANTY		3 years, 1years or 1000 hours



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Headquarters:
381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific:
9F, No. 1 92 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
www.viewsonic.com.tw

ViewSonic Singapore:
1 Kaki Bukit Road 1,
#03-40 Enterprise One,
Singapore 415934

ViewSonic Australia:
Unit 4, 44 Dickson Ave, Artarmor
NSW 2064, Australia
www.viewsonic.com.au

ViewSonic Korea:
#622, 6F, Gangbyeon Hanshin Core Bldg.,
350, Mapo-dong
Mapo-gu, Seoul 121-703, Korea

ViewSonic India:
Unit No 2, 3 &4, Ground Floor,
Tribhuvan Complex, Ishwar Nagar,
Mathura Road,
New Delhi - 110065

ViewSonic Middle East & South Africa:
Dubai U.A.E, PO 17625
me.viewsonic.com
ap.viewsonic.com / za

Rev.1.0

For more product information, visit us on the web at ViewSonic.com